

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 180 724 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
20.02.2002 Bulletin 2002/08

(51) Int Cl.⁷: **G03C 11/02**

(21) Application number: **01202890.8**

(22) Date of filing: **30.07.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Keech, John T.**
Rochester, New York 14650-2201 (US)
• **Spence, John P.**
Rochester, New York 14650-2201 (US)

(30) Priority: **09.08.2000 US 636058**

(71) Applicant: **EASTMAN KODAK COMPANY**
Rochester, New York 14650 (US)

(74) Representative:
Nunney, Ronald Frederick Adolphe et al
Kodak Limited, Patents, W92-3A, Headstone
Drive
Harrow, Middlesex HA1 4TY (GB)

(54) **A photographic element having a calibration patch**

(57) A photographic element, that includes a latent image of a reference calibration target having a two-dimensional barcode symbol with a finder feature and a reference calibration patch having a known spatial relation to the finder feature of the two-dimensional barcode symbol.

This element is preferably used in a method of locating a reference calibration patch on a photographic ele-

ment, that includes the steps of: exposing the photographic element to form the latent image of a reference calibration target; processing the photographic element to form a density image from the latent image; scanning the density image to produce a digital image; locating the finder feature of the two-dimensional barcode symbol in the digital image; and locating the reference calibration patch relative to the finder feature in the digital image.




Fig. 2

Description

[0001] The present invention relates to photography, and more particularly to photographic film having reference calibration patches and data.

[0002] The use of a sequence of reference calibration patches exposed on a roll of film to enable better exposure control during optical printing is known in the art. See for example US Patent No. 5,767,983 issued June 16, 1998 to Terashita. The use of calibration patches has also been shown to be useful in determining correction values for scanned film data used in digital printing. See for example US Patent No. 5,667,944 issued September 16, 1997 to Reem et al.; and US Patent No. 5,649,260, issued July 15, 1997 to Wheeler et al. It is also known to provide barcode data relating to film type and frame number on the edge of film for use in photofinishing.

[0003] The reference calibration patches used in these calibration procedures can be neutral, colored or any combination thereof. The neutral patches are created by using approximately equal red, green, and blue actinic exposures. Unfortunately, exposures which produce reference calibration patches that are of low contrast with respect to their background, such as obtained upon development of isolated low exposure areas on a color negative film, are difficult to locate with adequate accuracy in a digital image.

[0004] Depending on the application, many scanner types are used in the industry to obtain digital images. A scanner can employ a point sensor to acquire data one pixel at a time from a single, usually small, region of an image at one time and accumulate a full image by two-dimensional relative motion between the sensor and image. A scanner can employ a line array sensor to obtain a full line of pixels at a time and accumulate a two dimensional image by one dimensional relative motion between the sensor and image. A scanner can employ an area array detector and directly acquire a two dimensional image. The transport mechanism to feed a photographic element into a scanner can be one or more of many types, including a manual thrusting or positioning mechanism, a cartridge thrust mechanism, or a high speed continuous feed mechanism. Each class of scanner sensor and transport mechanism can introduce variation in the location and geometry of a digital image relative to the physical image due to variations in alignment, magnification, transport velocity, etc. All these variations make location of patches more difficult.

[0005] One solution to the problems of locating reference calibration patches is to additionally print easily identifiable and locatable features onto the photographic element, also called fiducial marks. See US Patent No. 5,198,907 issued March 30, 1993 to Walker et al. which discloses printing an L shaped registration mark having defined lengths relative to an exposure area in a scanner calibration original. The problem with printing such fiducial marks is that they require exposure apparatus and occupy valuable area on the photographic element, area that would preferably be used for additional reference sensitometric patches or other data.

[0006] A need remains to provide an improved method for locating sensitometric patches on photographic elements.

[0007] The need is met according to the present invention by providing a method of locating a calibration patch on a photographic element, that includes the steps of: exposing the photographic element to form a latent image of a reference calibration target having a two-dimensional barcode symbol with a finder feature and a calibration patch having a known spatial relation to the finder feature of the two-dimensional barcode symbol; processing the photographic element to form a density image from the latent image; scanning the density image to produce a digital image; locating the finder feature of the two-dimensional barcode symbol in the digital image; and locating the calibration patch relative to the finder feature in the digital image.

[0008] The method of the present invention has the advantage that no extra area on the photographic element is occupied by fiducial marks, thereby optimizing the use of the available area, since the standard two-dimensional barcode symbol already includes finding features that enable the reading of the barcode. These finding features are then used for the additional purpose of locating the reference calibration patches according to the present invention.

Fig. 1 is a schematic diagram showing a photographic element having a reference calibration target according to the present invention;

Fig. 2 is a schematic diagram showing a two-dimensional barcode symbol having a finding feature that defines more than one point;

Fig. 3 is a schematic diagram showing a plurality of two-dimensional barcode symbols each having a finding feature that defines a center point; and

Fig. 4 is a flow chart illustrating the method of the present invention.

[0009] An array of reference calibration patches are formed on a photographic element using exposures delivered using any of a variety of exposure modulation devices, preferably using a light source, an integrating chamber, and a fiber optic array with attenuating filters for determining exposure and an imaging head containing an array of lenses and field stops, each fiber exposing one reference calibration patch, as disclosed in copending U.S. Serial No. 09/635,389 by Bigelow et al. The number of reference calibration patches in the array is a function of the application. We prefer 23 patches for APS photographic film. A photographic element includes at least a base with a photosensitive

layer that is sensitive to light to produce a developable latent image. The photosensitive layer may contain conventional silver halide chemistry, or other photosensitive materials such as thermal or pressure developable chemistries. It can have a transparent base, a reflective base, or a base with a magnetically sensitive coating. The photographic element can be processed through standard chemical processes, including but not limited to Kodak Processes C-41 and its variants, ECN-2, VNF-1, ECP-2 and its variants, D-96, D-97, E-4, E-6, K-14, R-3, and RA-2SM, or RA-4; Fuji Processes CN-16 and its variants, CR-6, CP-43FA, CP-47L, CP-48S, RP-305, RA-4RT; Agfa MSC 100/101/200 Film and Paper Processes, Agfacolor Processes 70, 71, 72 and 94, Agfachrome Processes 44NP and 63; and Konica Processes CNK-4, CPK-2-22, DP, and CRK-2, and Konica ECOJET HQA-N, HQA-F, and HQA-P Processes. The photographic element can be processed using alternate processes such as apparently dry processes that may retain some or all of the developed silver or silver halide in the element or that may include lamination and an appropriate amount of water added to swell the photographic element. Depending upon the design of the photographic element, the photographic element can also be processed using dry processes that may include thermal or high pressure treatment. The processing may also include a combination of apparently dry, dry, and traditional wet processes. Examples of suitable alternate and dry processes include the processes disclosed in: US Serial Nos. 60/211,058 filed June 3, 2000 by Levy et al.; 60/211,446 filed June 3, 2000 by Irving et al.; 60/211,065 filed June 3, 2000 by Irving et al.; 60/211,079 filed June 3, 2000 by Irving et al.; EP Patent No. 0762201A1 published March 12, 1997, by Ishikawa et al.; EP Patent No. 0926550A1, published December 12, 1998, by Iwai, et al.; US Patent No. 5,832,328 issued November 3, 1998 to Ueda; US Patent No. 5,758,223 issued May 26, 1998 to Kobayashi, et al.; US Patent No. 5,698,382 issued December 16, 1997 to Nakahanada, et al.; US Patent No. 5,519,510 issued May 21, 1996 to Edgar; and US Patent No. 5,988,896 issued November 23, 1999 to Edgar. It is noted that in the processes disclosed by Edgar, development and scanning of the image occur simultaneously. Accordingly, it is the intent of the present invention that any development and scanning steps can be performed simultaneously.

[0010] As disclosed in copending application US Serial No. 09/635,600 by Keech et al., it is useful to store calibration data along with the reference calibration patches exposed onto photographic elements to aid in the calibration process. Such data is preferably stored using two-dimensional barcode symbols optically printed onto the photographic element. The combination of barcode data and reference calibration patches is collectively referred to as a reference calibration target. By placing the reference calibration target into a standard image frame as disclosed in copending application US Serial No. 09/635,496 by Keech et al., standard photofinishing film scanning apparatus can be used to acquire a digital image of the target. The scanning apparatus can employ a point sensor, a line sensor, or an area array sensor as described above.

[0011] Use of two-dimensional barcode symbols to store data is well known in the prior art and many such symbols have been standardized by national and international standards organizations. For example, the Data Matrix symbology, disclosed in US Patent No. 4,939,354 issued July 3, 1990 to Priddy et al., is the subject of the standards ANSI/AIM BC-11-1997 and ISO/IEC 16022:2000. A second such example, the MaxiCode symbology, disclosed in US Patent No. 4,874,936 issued October 17, 1989 to Chandler et al., is the subject of the standards ANSI/AIM BC-10-1997 and ISO/IEC 16023:2000. A third such example, the Aztec Code symbology, disclosed in US Patent No. 5,591,956 issued January 7, 1997 to Longacre, et al., is the subject of the standard ANSI/AIM BC-13-1998. Such two-dimensional symbols advantageously contain finding features designed to facilitate location of a symbol in a digital image containing a symbol using automatic procedures. Further, software used to locate such symbols in a digital image is readily available. For example, software for locating and decoding the Data Matrix and MaxiCode symbology is available as the Swift-Decoder™ software product from Omniplanar Inc., Princeton, NJ.

[0012] Referring to Fig. 1, a reference calibration target 11 useful with the method of the present invention is shown on a photographic element 10. The reference calibration target 11 includes an array 16 of two-dimensional barcode symbols 17, and an array 14 of reference calibration patches 15. The reference calibration target 11 is located on the photographic element 10 with respect to a perforation 12. Each barcode symbol 17 includes a finding feature that enables a software program to locate and decode the barcode symbol.

[0013] Referring to Fig. 2, a two-dimensional barcode symbol of the type having an L-shaped finding feature 19 (for example the Data Matrix symbology described above) that allows the decoding software to locate at least three reference points 19O, 19X and 19Y at the corners of the barcode symbol 17 is shown. A reference calibration patch 15 with a center location 21 is located at a known location with respect to the finding feature 19 of the two-dimensional barcode symbol 17. The center location 21 can be expressed for example in a Cartesian coordinate system that includes the locations of the three reference points 19O, 19X and 19Y of the two-dimensional barcode symbol 17. The known location 21 may be directly encoded as data in the two-dimensional barcode symbol or stored in an external database (not shown). A digital image area 13 containing the reference calibration target 11 is also shown.

[0014] Referring to Fig. 3, an array of two-dimensional barcode symbols 17 of the type having a center finding feature 25 comprising a set of concentric squares or rings (for example the Aztec symbology as shown or MaxiCode symbologies described above respectively) that allows the decoding software to locate the centers 25O, 25X and 25Y of the corresponding two-dimensional barcode symbols is shown. A reference calibration patch 15 with a center location 21

is located at a known location with respect to the centers **25O**, **25X** and **25Y** of the center finding features **25**. The center location **21** can be expressed for example in a Cartesian coordinate system that includes the locations of the centers **25O**, **25X** and **25Y** of the center finding features **25**. The known location **21** may be directly encoded as data in the two-dimensional barcode symbol or stored in an external database (not shown). A digital image area **13** containing the reference calibration target **11** is also shown.

[0015] Referring to Fig. 4, the method of the present invention includes the step of first exposing **(40)** the reference calibration target to form a latent image on a photographic element such as a film strip. The reference calibration target can be exposed onto the photographic element during manufacture, or at any time thereafter prior to processing. At a photofinisher, the photographic element is processed **(41)** to develop a density image of the reference calibration target. The density image of the reference calibration target is then scanned **(42)** in a conventional scanner to produce a digital image. The two-dimensional barcode symbols are then read from the digital image using conventional two-dimensional barcode reading software and the reference points of the two-dimensional barcode symbols are located **(43)** within the digital image. The reference calibration patch is located relative to the finder feature in the digital image as follows. Using the located reference points, the parameters of a transformation representing any distortion of the reference calibration target is computed **(44)**. Finally, the reference calibration patch coordinates are transformed **(45)** using the transformation parameters.

[0016] Such a transformation can take many forms, but for the purposes of the present invention, we have found that an affine linear transformation given by the matrix-vector equation

$$v = A u + b \quad \text{Eq.1}$$

wherein **u** is a two-dimensional vector of coordinates of a point in a first coordinate system, **v** is a two-dimensional vector of coordinates of the point in a second coordinate system, **A** is an invertible 2 by 2 matrix, and **b** is a two-dimensional shift vector, is particularly useful as it can be used to represent a wide variety of distortions that naturally arise in exposing and scanning such as those induced by shifting, scaling, rotation, skew, or combinations thereof. The particular six entries in the matrix **A** and vector **b** are parameters of the transformation that are completely determined by six values taken from the coordinate vectors **u** and **v** of three non-collinear points in the first and second coordinate systems respectively.

[0017] For example, referring again to Fig. 2, a two-dimensional (x,y) relative coordinate system for the reference calibration target **11** may be defined using the reference point **19O** as the origin (0,0), the point **19X** as a unit point in the first coordinate (1,0), and the point **19Y** as a unit point in the second coordinate (0,1). The known location (xc,yc) of the center point **15** in this relative coordinate system is defined by the geometry of the exposure apparatus used to form the latent image. A two-dimensional (k,l) pixel coordinate system for the digital image **13** formed of 'm' rows and 'n' columns of pixels may be defined using the point **13O** as an origin (0,0), the point **13N** as a point in the first coordinate (n-1,0), and the point **13M** as a point in the second coordinate (0,m-1). The locations of the reference points **19O**, **19X**, and **19Y** found in step **(43)** of Fig. 4 in this pixel coordinate system are defined as (ko,lo), (kx,lx), and (ky,ly) respectively. The location (k,l) of a point in the pixel coordinate system can be easily computed by applying an affine linear transformation of the form of Eq. 1 to the location (x,y) of the point in the relative coordinate system, with the parameters of this relative-to-physical coordinate transformation given directly in terms of the pixel coordinates of the reference points **19O**, **19X**, and **19Y**, as shown in Eq. 2:

$$\begin{bmatrix} k \\ l \end{bmatrix} = \begin{bmatrix} kx - ko & lx - lo \\ ky - ko & ly - lo \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} + \begin{bmatrix} ko \\ lo \end{bmatrix} \quad \text{Eq. 2}$$

In particular, the final patch coordinate transformation step **(45)** of Fig. 4 may be accomplished by transformation of the location (xc,yc) of the center point **15** into pixel coordinates (kc,lc) in the digital image using the transform in Eq. 2.

[0018] Referring now to Fig. 3, a two-dimensional (x,y) relative coordinate system for the reference calibration target **11** may be defined using the reference point **25O** as the origin (0,0), the point **25X** as a unit point in the first coordinate (1,0), and the point **25Y** as a unit point in the second coordinate (0,1). The known location (xc,yc) of the center point **15** in this coordinate system is defined by the geometry of the exposure apparatus used to form the latent image and is stored in either the bar code itself, or in an external memory as described previously. A two-dimensional (k,l) pixel coordinate system for the digital image **13** formed of 'm' rows and 'n' columns of pixels may be defined using the point **13O** as an origin (0,0), the point **13N** as a point in the first coordinate (n-1,0), and the point **13M** as a point in the second coordinate (0,m-1). The locations of the reference points **25O**, **25X**, and **25Y** found in step **(43)** in the pixel coordinate

system are again called (k_o, l_o) , (k_x, l_x) , and (k_y, l_y) respectively, and the location (k, l) of a point in the pixel coordinate system with coordinates (x, y) in the relative coordinate system can again be computed using Eq. 2. Again, the final step (45) of Fig. 4 may be accomplished by transformation of the location (x_c, y_c) of the center point 15 into pixel coordinates (k_c, l_c) in the digital image using the transform in Eq. 2.

[0019] More generally, rather than using a relative coordinate system based on the locations of three reference points within the reference calibration target 11 such as 19O, 19X, and 19Y in Fig. 2, or 25O, 25X, and 25Y in Fig. 3 respectively, to define a basic coordinate system for the reference calibration target, a physical two-dimensional coordinate system is used to locate points within the reference calibration target 11. Such a physical coordinate system can be based on physical features of the photographic element, for example, the location of a reference perforation 12 (see Fig. 1) and the edge of the photographic element 10 nearest the perforation, the axis directions being determined by the length and width of the film strip and being measured in convenient units. The procedure outlined in the above discussion of Figs. 2 and 3 can be used to define a second affine linear transformation of the form of Eq. 1, this time using given locations of the same three non-collinear reference points in the physical coordinate system, to obtain the transform parameters for a relative-to-physical coordinate transformation. This relative-to-physical coordinate transformation can be inverted using well known methods of linear algebra to form a physical-to-relative coordinate transformation, which is also an affine linear transformation of the form of Eq. 1. By applying the physical-to-relative and relative-to-pixel coordinate transformations in seriatim, locations specified in physical coordinates are transformed into pixel coordinates. The physical-to-pixel coordinate transformation obtained by such successive application of affine linear transformations is itself an affine linear transformation with parameters computed from the parameters of the individual transformations using well-known methods of linear algebra.

[0020] In a dedicated system with excellent control of digital image size and orientation relative to physical image size and orientation, the physical coordinate system can conveniently be defined in units commensurate with digital image pixels and aligned to share coordinate directions with the digital image coordinate directions. In such a case, the physical-to-pixel coordinate transformation takes the form of a pure translation, with the matrix A in Eq. 1 being an identity matrix and the only free parameters being the two entries in the shift vector b in Eq. 1. These parameters of this transform are completely determined by physical and pixel coordinates of a single point. The computation in step (44) of Fig. 4 becomes subtraction of physical coordinates from pixel coordinates.

[0021] In a dedicated system with excellent control of digital image orientation relative to physical image orientation, the physical coordinate system can conveniently be aligned to share coordinate directions with the digital image coordinate directions. In such a case, the physical-to-pixel coordinate transformation takes the form of a translation and scaling transform, with the matrix A in Eq. 1 being a diagonal matrix with two free parameters and the shift vector b in Eq. 1 comprising two additional free parameters. These four parameters are completely determined by the physical and pixel coordinates of two points that do not share a common coordinate value in either coordinate system. The parameter computation in step (44) of Fig. 4 becomes subtraction of physical coordinates from pixel coordinates of either point and forming the ratios of pixel coordinate differences and physical coordinate differences between the two points.

[0022] Further, use of locations of more than the minimum required number of reference points to obtain parameters in step (44) of Fig. 4 using well-known methods such as ordinary least squares, can be advantageous in the presence of naturally arising uncertainty in locations in a digital image.

Claims

1. A photographic element, comprising:
 - a) a base;
 - b) a photosensitive layer on the base; and
 - c) a latent image in the light sensitive layer of a reference calibration target having a reference calibration patch and a two-dimensional barcode symbol with a finder feature having a known spatial relation between the reference calibration patch and the finder feature of the two-dimensional barcode symbol.
2. The photographic element claimed in claim 1, the known spatial relation is the location of the center of the reference calibration patch.
3. The photographic element claimed in claim 1, wherein the finding feature of the two-dimensional barcode symbol locates the corners of the two-dimensional barcode symbol.
4. The photographic element claimed in claim 1, wherein the finding feature of the two-dimensional barcode symbol

locates the center of the two-dimensional barcode symbol.

5. The photographic element claimed in claim 1, wherein the reference calibration target comprises an array of two-dimensional barcode symbols.
6. The photographic element claimed in claim 1, wherein the photographic element is a film strip.
7. The photographic element claimed in claim 1, wherein the photosensitive layer contains conventional silver halide chemistry.
8. The photographic element claimed in claim 1, wherein the photosensitive layer contains thermal developable chemistry.
9. The photographic element claimed in claim 1, wherein the photosensitive layer contains pressure developable chemistry.
10. The photographic element claimed in claim 1, wherein the location of the reference calibration patch relative to the finder feature is stored in the two-dimensional barcode symbol.
11. The photographic element claimed in claim 1, wherein the photographic element is an APS film strip, and the reference calibration target includes 23 reference calibration patches and 6 two-dimensional barcode symbols.




Fig. 1




Fig. 2




Fig. 3





FIG. 4



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 180 724 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
07.05.2003 Bulletin 2003/19

(51) Int Cl.⁷: **G03C 11/02**

(43) Date of publication A2:
20.02.2002 Bulletin 2002/08

(21) Application number: **01202890.8**

(22) Date of filing: **30.07.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Keech, John T.**
Rochester, New York 14650-2201 (US)
• **Spence, John P.**
Rochester, New York 14650-2201 (US)

(30) Priority: **09.08.2000 US 636058**

(74) Representative: **Haile, Helen Cynthia et al**
Kodak Limited
Patent, W92-3A,
Headstone Drive
Harrow, Middlesex HA1 4TY (GB)

(71) Applicant: **EASTMAN KODAK COMPANY**
Rochester, New York 14650 (US)

(54) A photographic element having a calibration patch

(57) A photographic element, that includes a latent image of a reference calibration target having a two-dimensional barcode symbol with a finder feature and a reference calibration patch having a known spatial relation to the finder feature of the two-dimensional barcode symbol.

This element is preferably used in a method of locating a reference calibration patch on a photographic ele-

ment, that includes the steps of: exposing the photographic element to form the latent image of a reference calibration target; processing the photographic element to form a density image from the latent image; scanning the density image to produce a digital image; locating the finder feature of the two-dimensional barcode symbol in the digital image; and locating the reference calibration patch relative to the finder feature in the digital image.




Fig. 2



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 20 2890

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
D,A	US 5 667 944 A (REEM ET AL) 16 September 1997 (1997-09-16) * column 6, line 48 - line 56 * * column 7, line 41 - column 8, line 16 * * figures 1,2 * * claims 1-4,12,14,19,25 *	1-11	G03C11/02
A	US 5 563 717 A (KOENG ET AL) 8 October 1996 (1996-10-08) * column 1, line 7 - line 14 * * column 5, line 22 - line 49 * * figure 2 * * claims 1,2 *	1-11	
D,A	US 5 591 956 A (LONGACRE, JR. ET AL) 7 January 1997 (1997-01-07) * column 1, line 7 - line 13 * * column 2, line 23 - line 34 * * claims 1,11,20 *	1-11	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7) G03C H04N
Place of search MUNICH		Date of completion of the search 18 March 2003	Examiner Binder, R
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 20 2890

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-03-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5667944	A	16-09-1997	EP 0770905 A2	02-05-1997
			JP 9197577 A	31-07-1997
US 5563717	A	08-10-1996	NONE	
US 5591956	A	07-01-1997	US 5900613 A	04-05-1999
			US 5932862 A	03-08-1999
			US 5825006 A	20-10-1998
			US 5929418 A	27-07-1999
			US 5965863 A	12-10-1999